

Features



OPTIONAL POWER FEEDER FOR TILE



**3", 4", 5", 6", 8", 10" OR 12"
INTERCHANGEABLE TILE BOOT**



HEAVY DUTY COMMERCIAL GRADE FRAME

Frame mounted tile plow burys up to 6ft. deep

Quick Change Boot Design to match size of your tile so you have optimum tile support and minimum drag equal to the width of your tile. Helps prevent stretch. A single removable rod pin makes changing boots easy. Boot sizes available – 3" up to 12".

Lower Angle Plow design results in a low drawbar pull with minimal smearing and maximum shatter of trench.

Two Sets of Hydraulic Cylinders - upper cylinders adjust altitude and lower cylinders adjust down pressure.

Knife Edged with Stainless Steel opens the ground first to allow the boot to glide through and provide accurate placement of tile.

Tile Feed Guide for 4", 5" or 6" tile keeps tile in place for quick accurate feed.

Water Level indicates at a glance whether you are on level.

Optional Power Feeder is hydraulic driven - low volume and feeds 4", 5" or 6" pipe. Easy to install, the Power Feeder is maintenance free. Minimizes any stretching of plastic pipe and protects longevity and working capacity.

Heavy Duty Frame constructed for rugged durability and made to last.

Adjustable Valve for draft control.

Optional Equipment

GPS Grade Control • Laser Grade Control

**Hydraulic Mast with 42" Stroke • Power Feeder
Stringer Trailer • Plow Caddy • Steerable Plow**

Frame Mounted Steerable Plow

This plow is designed to mount close to the tractor to provide maximum traction as both tracks pull all the time making it easy to follow the natural flow of the ground. Because the plow is mounted high on the tractor it transfers the weight to the front of the tractor for added stability.

The plow stays vertical when turning corners. You steer the tractor with the plow like a boat rudder. There is not a cart on wheels to back up in the field.



Steerable Plow Option