

Quick Tach hookup in 10 minutes!

Quick Tach Receiver Bracket provides an easy hookup in 10 to 15 minutes using a Hitch pin and C-clips to mount the Tile Pro to your tractor. Easy hookup is not the only reason to buy a frame mounted tile plow. The Quick Tach is used to attach the Tile Pro to the frame of the tractor—not the 3-point hitch—giving the Tile Pro better stability for grade than the standard pull type plow.



STX Quick Tach



CAT CHALLENGER 965B QUICK TACH



3-POINT HOOKUP

Tile Pro Comparison Chart Three Models to Choose From.

SPECS	5 FT.	6 FT.	7 FT.
Weight	3800 lbs.	7000 lbs.	9000 lbs.
Height	9' 6"	10' 6"	11' 6"
Length	8'	12'	12'
Cylinder Size	(2) 4" x 36"	(2) 4.5" x 36"	(2) 5" x 36"
Top Cylinder	(1) 6" x 12"	(2) 6" x 12"	(2) 7" x 12"
Max. Operating Depth	5'	6'	7'
Min. H.P.	200 H.P./FWA	250-450 H.P.	350-650 H.P.
Main Shank	2 1/4" Grade 50	4 1/4" Grade 50	4 3/4" Grade 50
Main Frame	3" x 6" x 3/8"	3" x 6" x 3/8"	3" x 8" x 3/8"
	Double Rec. Tubing	Triple Rec. Tubing	Tripled Rec. Tubing
A-Frame	1" x 6" Flat Iron	1" x 6" Flat Iron	1" x 6" Flat Iron
Parallel Linkage	42" C.T.C.	42" C.T.C.	42" C.T.C.
Pivot Pins	2 1/16" Diameter	2 1/16" Diameter	2 1/2" Diameter
Main Pins	3" Diameter	3" Diameter	3 1/2" Diameter
Aux. Hitch	Yes	Yes	Yes
St. Steel Knife Sides	No	Yes	Yes
Storage Jacks	Yes	Yes	Yes
Water Level	Standard	Standard	Standard
Adjustable Valve	Standard	Standard	Standard

OPTIONS

Knife & Boot Sizes	4", 5", 6"	4", 5", 6", 8", 10", 12"	4", 5", 6", 8", 10", 12"
Quick Tach	Yes	Yes	Yes
Power Feeder	Yes	Yes	Yes
St. Steel Skinned Boots	Yes	Yes	Yes
UHMWPE Skinned Boots	Yes	Yes	Yes
Hydraulic Mast	Yes	Yes	Yes
Rigid Mast	Yes	Yes	Yes
Steerable Linkage (for Track Machines)	Yes	Yes	Yes



CAT 865 STEERABLE PLOW