

# Dig, lay and bury drainage tile... in one pass!

## Advantages of Frame-Mounted Tile Plow:

- Designed to work like a commercial grade plow when frame mounted to your tractor or dozer.
- Pulls easier because of even transfer of weight to front and rear ends for traction.
- Better stability for grade control than pull type. • More trash clearance.
- Knife opens the ground first to allow the boot to glide through.
- No wheels to back over starting hole or work around.



**PRO  
TILE**



## Ask About Our Tile Pro Cost Comparison. Two Models to Choose From.

| SPECIFICATIONS                    | 5 FT.                          | 6 FT.                          |
|-----------------------------------|--------------------------------|--------------------------------|
| Weight                            | 3800 lbs.                      | 6300 lbs.                      |
| Height                            | 9' 6"                          | 10' 6"                         |
| Length                            | 8' 0"                          | 12' 0"                         |
| Cylinder Size                     | 2 = 4" x 36"                   | 2 = 4.5" x 36"                 |
| Top Cylinders                     | 2 - 6 x 12                     | 2 - 6 x 12                     |
| Max. Operating Depth              | 5'                             | 6'                             |
| Sugg. Min. HP                     | 200 HP/FWA                     | 250 - 300 HP                   |
| Main Knife                        | 2 1/4" Grade 50                | 4 1/4" Grade 50                |
| Main Frame                        | 6 x 3 x 3/8 Rec Tubing-Doubled | 6 x 3 x 3/8 Rec Tubing-Tripled |
| A-Frame                           | 1 x 6 Flat Iron                | 1 x 6 Flat Iron                |
| Parallel Linkage                  | 42" C.T.C.                     | 42" C.T.C.                     |
| Pivot Pins                        | 2 1/8" Dia.                    | 2 1/8" Dia.                    |
| Main Pins                         | 3" Dia.                        | 3" Dia.                        |
| Auxiliary Hitch for Towing        | Yes                            | Yes                            |
| Lined Stainless Steel Knife Sides | Yes                            | Yes                            |
| Storage Jacks                     | Yes                            | Yes                            |

### OPTIONS

|                                                    |             |                        |
|----------------------------------------------------|-------------|------------------------|
| Knife & Boot Sizes                                 | 3, 4, 5, 6" | 3, 4, 5, 6, 8, 10, 12" |
| Quick Tach                                         | Yes         | Yes                    |
| Power Feed                                         | Yes         | Yes                    |
| Steerable Linkage for Track Machine for 6 ft. Plow |             | Yes                    |

1. Adjustable upper hydraulic linkage for laser control.
2. Tile feed guide for 4", 5" or 6" tile or "power feeder".
3. Boot pivots 30 degrees both ways.
4. Single full-length removable rod pin to interchange tile boots from 3" to 12".
5. Easy to change the boot in the field.
6. Smaller main knife pushes dirt up and out.
7. Cutting knife face and tile boot are same size for easier pull.
8. Two removable pins on each side for interchangeable knife face.
9. Side of knife lined with stainless steel for less resistance and drag through the ground.
10. Fast hookup, drawbar and upper receiver bracket.